

**CLASSIC
COLLECTION**
—by Somerset™—



NATURAL RED OAK
Red Oak

GUNSTOCK
Red Oak

CHERRY OAK
Red Oak

URBAN GRAY
Red Oak

SABLE
Red Oak

BUTTERSCOTCH
Red Oak

MYSTIC
Red Oak

APPALACHIAN OAK FLOORING
WITH A LIGHTLY TEXTURED SURFACE
FOR A MORE DURABLE APPEARANCE.



S SOLID
3/4" thick, random lengths up to 6-1/2'
WIDTHS: 2-1/4", 3-1/4"

S SOLIDPLUS™ ENGINEERED
1/2" thick, 3mm thick solid sawn wear
layer, 8-ply, random lengths up to 6-1/2'
WIDTHS: 3-1/4", 5"



PRODUCT SPECIFICATION SHEET

02/14

CLASSIC: SOLID



Product:	Somerset Classic Collection Solid Hardwood Flooring			
Species:	Red Oak (Somerset does not mix species.)			
Grade:	Proprietary Somerset grade that meets or exceeds NOFMA Standard and Better.			
Dimensions:	Thickness: 3/4"* Widths: 2-1/4", 3-1/4" Lengths: Random from 10" up to 6-1/2' (conforms to NOFMA Standard and Better specification) <small>*Nominal</small>			
Construction:	Traditional 3/4" solid construction produced from domestically grown and harvested Appalachian hardwood. Material conforms to Appalachian Hardwood Manufacturers, Inc.'s Verified Sustainable Seal (www.appalachianwood.org). Product is also affiliated with National Oak Flooring Manufacturers Association and the National Wood Flooring Association.			
Profile:	Eased Edge, Square End			
Finish:	Ultimate™ Urethane Finish — UV Cured Aluminum Oxide, Abrasion Resistant Finish			
Colors:	2 1/4" Width	3 1/4" Width	Species	
	Natural Red Oak	CL2101	CL3101	Red Oak
	Gunstock	CL2104	CL3104	Red Oak
	Cherry Oak	CL2105	CL3105	Red Oak
	Urban Gray	CL2107	CL3107	Red Oak
	Sable	CL2108	CL3108	Red Oak
	Butterscotch	CL2109	CL3109	Red Oak
	Mystic	CL2110	CL3110	Red Oak
Gloss Level:	Low Gloss			
Janka Hardness:	Species	Lbs		
	Red Oak	1290		
MSDS:	Not required for cured finish, MSDS for Wood Dust available on request			
Flame Spread:	Class C			
Installation:	Nail down or staple, on or above grade. (NWFA Installation Guidelines and Methods, revised: March, 2007.) Installation guidelines are printed on the bottom of each carton and available at www.somersetfloors.com .			
Maintenance:	Somerset Ultimate™ Wood Floor Cleaner (www.somersetfloors.com)			
Limited Warranty:	50-Year Finish Wear; Lifetime Structural Integrity (www.somersetfloors.com)			
Molding:	Quarter Round, Stair Nose, Threshold, T-Mold, and Reducer			

PRODUCT SPECIFICATION SHEET

CLASSIC: SOLID**PLUS**™ ENGINEERED



Product:	Somerset Classic Collection Solid Plus Engineered Hardwood Flooring			
Species:	Red Oak (Somerset does not mix species.)			
Grade:	Proprietary Somerset grade that meets or exceeds NOFMA Standard or Better.			
Dimensions:	Thickness: 1/2"*; 3mm* thick solid dry sawn wear layer Widths: 3-1/4", 5" Lengths: Random from 10" up to 6-1/2' <small>*Nominal</small>			
Construction:	8-ply cross-grain engineered construction; 7-ply birch core.			
Profile:	Eased Edge, Eased End			
Finish:	Ultimate™ Urethane Finish — UV Cured Aluminum Oxide, Abrasion Resistant Finish			
Colors:	3 1/4" Width	5" Width	Wear Layer Species	
	Natural Red Oak	EP314CLROE	EP512CLROE	Red Oak
	Gunstock	EP314CLGUE	EP512CLGUE	Red Oak
	Cherry Oak	EP314CLCOE	EP512CLCOE	Red Oak
	Urban Gray	EP314CLUGE	EP512CLUGE	Red Oak
	Sable	EP314CLSBE	EP512CLSBE	Red Oak
	Butterscotch	EP314CLBUE	EP512CLBUE	Red Oak
	Mystic	EP314CLMYE	EP512CLMYE	Red Oak
Gloss Level:	Low Gloss			
Janka Hardness:	Species	Lbs		
	Red Oak	1290		
MSDS:	Not required for cured finish, MSDS for Wood Dust available on request			
Flame Spread:	Class C; ASTM E84 Flame Spread Index - 138			
Formaldehyde Emissions:	ASTM D6007; BLQ (beneath limit of qualification - .008ppm)			
Critical Radiant Flux (CRF):	ASTME648 - Test in Progress			
Installation:	Nail, staple, glue down, or float on, above or below grade (ground level). (NWFA Installation Guidelines and Methods, revised: March, 2007.) Installation guidelines are printed on the bottom of each carton and available at www.somersetfloors.com			
Maintenance:	Somerset Ultimate™ Wood Floor Cleaner (www.somersetfloors.com)			
Limited Warranty:	50-Year Finish Wear; Lifetime Structural Integrity (www.somersetfloors.com)			
Molding:	Quarter Round, Stair Nose, Threshold, T-Mold, and Reducer			